QUICK REFERENCE GUIDE > GDSBE1-302-L

30" Series 9 Griddle/Side Burner, LPG

Series 9



Get the best of both worlds with a Griddle and Dual Side Burner. Combining the quick cooking griddle with two side burners for sautéing and simmering, this is a hard working product for the outdoor kitchen where space is limited.

- Seamless installation and interconnectivity between products allows for unified operation, from ignition to dial illumination
- · Fast, weather resistant ignition system
- · Made from durable, hardwearing 304 stainless steel
- Able to be built-in or mounted on a freestanding cart (Grill Cart sold separately - CAD1-30E)

Height	10 1/2	
Width	30	
Depth	26 7/8	

FEATURES & BENEFITS

Cook It Your Way

Cook it your way with a variety of flexible cooking methods provided by DCS cooking attachments.

Designed To Match

With a matching look across all DCS Series 9 products, you can create a stylish, cohesive design for your Outdoor kitchen. Seamless installation and interconnectivity between products* allows for unified operation, from ignition to dial illumination.

Convenient And Reliable

Illuminated dials immediately and intuitively tell you at a glance if the product is on. Get grilling quickly with a fast, weather resistant ignition system that works every time.

Durable And Hard Wearing

Made from durable, hardwearing 304 stainless steel with stainless steel weather covers to ensure they are protected from the elements.

SPECIFICATIONS

Accessories (sold separately)

Optional cart mount CAD1-30E

Burners

Number of side burners	2
Number of U-burners	1

Cooking Surface Area

Total cooking area 244 sq.in.

Features

Griddle plate

Ignition system

Side burners

Stainless steel cover included

•

Finish

Available in built-in or on cart applications

Material

304 grade stainless steel

Weather resistant

Gas Requirements

1/2" NPT male with 3/8" in flare adapter

Gas type

LP hose with regulator and Type 1 connector

Operational pressure

11" W.C.

Supply pressure

12" to 14" W.C.

Installation Dimensions

Cutout depth (proud) 22 3/4 "





QUICK REFERENCE GUIDE > GDSBE1-302-L Date: 24.09.2025 > 2

Cutout height (proud)	10 1/8 "	↓ Installation Guide EN
Cutout width (proud)	28 1/2 "	
Cutout width (proud)	20 1/2	Planning Guide EN - Professional Grills Series 9 Out Kitchen
Performance		Planning Guide FR - Professional Grills Series 9 Out Kitchen
Side burner power	17000 BTU	Planning Guide SP - Professional Grills Series 9 Outo Kitchen
Total Power	46000 BTU	→ Revit-18 Griddle Side Burner
U-burner power	12000 BTU	→ Rhino-5 Griddle Side Burner
		Rhino-5 Griddle Side Burner with Insulated Jacket
		Service and Warranty EN FR Service and Warranty E
Power requirements		
Power and logic interconnectivity	•	SketchUp-8 Griddle Side Burner with Insulated JackUser Guide EN
Supply frequency	60Hz	± ↓ User Guide FR
Supply voltage	120 V	<u>*</u>
		A PEACE OF MIND SALE
Warranty		24 Hours 7 Days a Week Customer Support
•		T 1.888.936.7872 W www.dcsappliances.com
Parts and labor	2 years	

71470

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

Other product downloads available at dcsappliances.com

SKU