48" Grill, Natural Gas

Series 7				
Stainless Steel	I	Natural gas		



Designed with flexibility in mind, DCS Grills allow you to cook a wide variety of meals and are engineered to deliver the functionality and power demanded by a professional chef. DCS Grills are hand-finished to perfection to complement the quality of the DCS premium outdoor kitchen and built to withstand the demands of the serious cook and the extremes of mother nature. Available in Natural and LP Gas.

48" Grill

DIMENSIONS

Height	24 1/4″
Width	47 7/8″
Depth	26 5/8″

FEATURES & BENEFITS

Precision heat and control

A DCS Grill puts you in control of up to a massive 121,500 BTU per hour total power. That power lets you choose the precise heat you need from a low and slow 300° up to an intense 1100°. DCS Grills do more than help you grill an incredible steak, you can infuse smoke into your favorite meal using the built in smoker, or close the specially designed hood and use the power of convection to cook the perfect pizza. DCS Grills put you in control, giving you the versatility to cook what you want.

Double-sided Cast Stainless Steel Grates

One side has a gentle radius for handling delicate foods. The other side is W-shaped for perfect sear lines while channeling oil away to an easily removable drip tray.

Grease Management System™ Grease Channeling Technology

This patented technology reduces flare-ups by directing grease and oils away from the burner flames during grilling.

Smart Beam[™] Grill Light

A halogen light is designed to illuminate the entire cooking surface for perfect night grilling.

Temperature Gauge - zero to sear

Go from zero to sear with DCS Grills' new built-in temperature gauge. It lets you know exactly how hot the grill is, even when the hood is down.

Dedicated Sealed Smoker



A dedicated smoker tray with a direct 3,500BTU burner offering a clean, convenient option for specialized smoking recipes.

SPECIFICATIONS

Accessories (sold separately	
	n

6" accessory storage	ASH6-48
Built-in grill cover	ACBI-48
Griddle plate	BGC-GP
Hybrid IR burner	BGC-IR
Insulated jacket	BGA48-IJS (optional)
Insulated jacket (with storage	BGA54-IJS (optional)
On cart grill cover	ACC-48
Optional cart mount	CAD1-48

Burners

Number of U-burners	4
Cooking Surface Area	
Primary cooking area	855sq.in.
Total cooking area	1182sq.in.
Warming rack area	327sq.in.

Features

Double sided Stainless Steel	•
Full surface searing	•
Grease management system™	•
Hood temperature gauge	•
Ignition system	Spark
Metal dials	•

QUICK REFERENCE GUIDE > BH1-48R-N

Smoker • Warming rack • Finish Material 304 grade stainless steel Weather resistant • Gas Requirements 1/2" NPT male with 3/8" in flare • Gas type NG Operational pressure 4" W.C. Supply Pressure 6" to 9" W.C. Installation Dimensions Cutout depth (proud) 22 3/4" Cutout depth (proud) 10 1/8" Cutout width (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance Rotisserie burner power 18000 BTU		
Warming rack • Finish Material 304 grade stainless steel Weather resistant • Gas Requirements 1/2" NPT male with 3/8" in flare • Gas type NG Operational pressure 4" W.C. Supply Pressure 6" to 9" W.C. Isupply Pressure 6" to 9" W.C. Installation Dimensions Cutout depth (proud) 22 3/4" Cutout height (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance Rotisserie burner power 18000 BTU	Rotisserie	•
Finish Material 304 grade stainless steel Weather resistant • Gas Requirements 1/2" NPT male with 3/8" in flare • Gas type NG Operational pressure 4" W.C. Supply Pressure 6" to 9" W.C. Installation Dimensions Cutout depth (proud) 22 3/4" Cutout height (proud) 10 1/8" Cutout width (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance Rotisserie burner power 18000 BTU	Smoker	•
Material 304 grade stainless steel Weather resistant • Gas Requirements • 1/2" NPT male with 3/8" in flare • Gas type NG Operational pressure 4" W.C. Supply Pressure 6" to 9" W.C. nstallation Dimensions • Cutout depth (proud) 22 3/4" Cutout width (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance Rotisserie burner power 18000 BTU	Warming rack	
Weather resistant Gas Requirements 1/2" NPT male with 3/8" in flare Gas type NG Operational pressure 4" W.C. Supply Pressure 6" to 9" W.C. nstallation Dimensions Cutout depth (proud) 22 3/4" Cutout height (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance Rotisserie burner power 18000 BTU	Finish	
Gas Requirements 1/2" NPT male with 3/8" in flare Gas type Gas type Operational pressure 4" W.C. Supply Pressure 6" to 9" W.C. nstallation Dimensions Cutout depth (proud) 22 3/4" Cutout height (proud) 10 1/8" Cutout width (proud) 10 1/8" Insulated jacket for proud cut- Varies - check manual Performance Rotisserie burner power	Material	304 grade stainless steel
1/2" NPT male with 3/8" in flare NG Gas type NG Operational pressure 4" W.C. Supply Pressure 6" to 9" W.C. nstallation Dimensions 6" to 9" W.C. Cutout depth (proud) 22 3/4" Cutout height (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance 18000 BTU	Weather resistant	
Gas type NG Operational pressure 4" W.C. Supply Pressure 6" to 9" W.C. nstallation Dimensions 6" to 9" W.C. Cutout depth (proud) 22 3/4" Cutout height (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance 18000 BTU	Gas Requirements	
Operational pressure 4" W.C. Supply Pressure 6" to 9" W.C. nstallation Dimensions 22 3/4" Cutout depth (proud) 22 3/4" Cutout height (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance 18000 BTU	1/2" NPT male with 3/8" in flare	•
Supply Pressure 6" to 9" W.C. nstallation Dimensions 10 1/8" Cutout depth (proud) 10 1/8" Cutout height (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance 18000 BTU	Gas type	NG
nstallation Dimensions Cutout depth (proud) 22 3/4" Cutout height (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance Rotisserie burner power 18000 BTU	Operational pressure	4″ W.C.
Cutout depth (proud) 22 3/4" Cutout height (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance 18000 BTU	Supply Pressure	6" to 9" W.C.
Cutout height (proud) 10 1/8" Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance 18000 BTU	Installation Dimensions	
Cutout width (proud) 45 3/4" Insulated jacket for proud cut- Varies - check manual Performance Rotisserie burner power 18000 BTU	Cutout depth (proud)	22 3/4"
Insulated jacket for proud cut- Varies - check manual Performance Rotisserie burner power 18000 BTU	Cutout height (proud)	10 1/8″
Performance Rotisserie burner power 18000 BTU	Cutout width (proud)	45 3/4"
Rotisserie burner power 18000 BTU	Insulated jacket for proud cut-	Varies - check manual
	Performance	
Smoker burner power 3500 BTU	Rotisserie burner power	18000 BTU
	Smoker burner power	3500 BTU

Product dimensions

Depth	26 5/8″
Height	24 1/4″
Packaged weight	348lbs
Width	47 7/8″
Width including rotisserie	56 3/8"
SKU	71444

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? DCS by Fisher & Paykel Appliances Limited 2020

Other product downloads available at dcsappliances.com

- ↓ Installation & User Guide EN / Guide d'installation et guide d'utilisation FR
- Service and Warranty
- Guide d'installation
- Installation Guide
- ➡ Data Sheet

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com

Power requirements

Weight rotisserie can handle

Total Power

U-burner power

Grill power supply	9V Battery for Ignition
Rotisserie power supply	120V 60Hz

121500 BTU

25000 BTU

50lbs